



USER MANUAL

BEBOB V95 RECHARGEABLE LITHIUM-ION BATTERY

THANK YOU FOR PURCHASING THE BEBOB V95 RECHARGEABLE LITHIUM-ION BATTERY.

PRIOR TO USING THE BEBOB V95 WE STRONGLY RECOMMEND THAT YOU READ THIS INSTRUCTION MANUAL ON HOW TO BEST USE THE BEBOB V95. YOU SHOULD KEEP IT FOR FUTURE REFERENCE. IF YOU HAVE ANY ADDITIONAL QUESTIONS, PLEASE CONTACT THE APPROPRIATE BEBOB DISTRIBUTOR LISTED AT WWW.BEBOB.DE.

FEATURE

- A high capacity battery which is compact and lightweight. Direct fitting to a camera via V-Mount.
- Five-step LED power indicator.
- One status overload indicator.

CHARGING BEBOB V95

- The bebob V95 battery can be charged with an external bebob charger (or equivalent) with Lithium-ion (Li-ion) charging ability.
- Approximate charge time may vary depending on charger and temperature.
- bebob V95 can be charged in ambient temperature for optimum performance at 10°C - 30°C.
- bebob V95 batteries can be recharged in any charge condition.

DISCHARGING BEBOB V95

- Maximum load is 7.0 A. When using the battery with video or lighting equipment, power consumption of the equipment must be 7.0 A or below. For the protection of the battery, a load of 7.0 A or over may activate the internal protection circuit and stop supply of power. In this case the status led will turn red.
- The battery can be used in ambient temperature of - 20°C - + 55°C.

STORING BEBOB V95

- Storage temperature range is - 20°C ~ + 35°C (<85% humidity).
- To store the battery for a long period (longer than 6 months), the battery should be fully charged and left in this condition. The bebob V95 should be recharged every six months.
- After storage some self discharge will occur. Before re-use it is advisable to recharge the battery fully.

PLEASE NOTE

- Before using this product please note the following general safety information.
- Read instruction manual before use. It is mandatory to follow the instructions in this manual.
- The operation instructions form part of the product and should be handed over to any future owner in the event of sale/transfer of the product.
- This manual should be retained for the life of the product.
- If you have any questions about this product, please ask only authorized specialist personnel for advice.

CAUTION

- Use only with recommended charger.
- Keep the battery dry and do not immerse in water.
- Never open the battery.
- Do not expose to temperature over 60°C.
- May explode if thrown into fire!
- Maximum load 7.0 A.
- Do not put the battery on a device when the red charging LED flashes.

SPECIFICATION

BATTERY

| | |
|----------------------------|---|
| CELL | Lithium-ion |
| VOLTAGE | DC 14.8V |
| CAPACITY | 6.6 Ah |
| MAXIMUM LOAD | 7.0 A |
| END VOLTAGE | 12.0 V |
| BATTERY PROTECTION CIRCUIT | Over-voltage, under-voltage, and over-current, outside circuit shortage and equilibrium in unconventional situations. |

GENERAL

| | |
|---------------------|-----------------------------|
| AMBIENT TEMPERATURE | |
| CHARGE | + 10°C ~ + 30°C recommended |
| DISCHARGE | - 20°C ~ + 55°C |
| STORAGE | - 20°C ~ + 35°C (<85% RH) |
| CHARGING TIME | 3 hours |
| MOUNTING | V-Mount |
| DIMENSIONS (WxHxD) | 89 x 175 x 46 mm |
| WEIGHT | 0.88 kg |

WARRANTY

- The V95 is covered by a 2 years warranty on all mechanical and electronical parts, except the cells
- The cells are covered by a 1 year warranty, 70% of the original capacity
- For warranty issues contact the appropriate bebob distributor listed at www.bebob.de